

SAFETY NOSING

Stair nosing are used to enhance safety feature of stair finishes. There are various types of stair nosing and the intended functional value varies on the type and size of the nosing used.

Aluminum nosing, are used not only to define the stair edges for added safety and oftentimes to improve slip resistance to an acceptable value.

OROFIL selection of stair nosing are evaluated and qualified to conform to standard slip resistance value with reference to ANSI B101.3 the standard measures the dynamic coefficient of friction (**DCOF**). Test using this standard is done using a sodium lauryl sulfate (SLS), an ingredient in many detergents, mixed in the water and used for the testing as wetting agent.

The standard establishes a minimum **DCOF** of not less than 0.42 for level floors. The slip test is within the acceptable low slip risk for human in dynamic motion.

All nosing under the types selected by OROFIL conforms to the above standard, the designer can explore the aesthetic options in using various nosing under our product lines with the assurance that all types are in conformance with the required ANSI standard with minimum anti slip factor requirement of not less than 0.42

TYPES OROFIL NOSING

OF-ASNC : ALUM w/ RUBBER INSSERT NOSING
SIZE : 60mm
MOUNTING : SCREW TYPE
COLOR : ALUM with black

OF-BF TYPE : BRASS NOSING, w/ GROOVE
SIZE : 50mm, 38mm
MOUNTING : CAST IN PLACE
COLOR : BRASS

OF-CBR : CARBORUNDUM STRIP, 3M or equiv
SIZE : 50mm
MOUNTING : INDUSTRIAL ADHESIVE
COLOR : BLACK & GRAY

ORO-FILIPINO ENT. & DEV'T. CORP - All products should be used in accordance with the manufacturer instruction. The manufacturer can take no responsibilities where conditions of used are beyond our control. Available for sale in accordance with Standard Conditions of Sale, available on request. Whilst any information and/or specification contained here in suggestion made by our Representative, or us Agents or Distributors as the conditions of use and any labour involved are beyond our control. I date sheet are updated on a regular basis. To ensure that this technical data sheet has not been superseded pleased contact ORO-FILIPINO ENT. & DEV'T. CORP. Some photos are taken from suppliers marketing materials and used as reference only

